



IC-V3MR

MULTI-USE RADIO SERVICE (MURS) TRANSCEIVER

License Free

IP54 and MIL-STD 810G
Tough and Rugged Body



2 Watts Output and All 5 MURS
Frequencies for Business Use

High Capacity Li-ion Battery
24 hours Operational Time
(5/5/90 duty)

Made in Japan Quality
Full Robotic Assembly

1500 mW (typ.) Powerful
Audio with BTL Amplifier



Optional 1500mW
Speaker-Microphone,
HM-222HLWP



Rugged, Loud and Reliable



2 Year
Warranty

Other Features

- VOX (Voice Operated Transmit) function
- MDC PTT ID transmit
- CTCSS Tone and DTCS code
- DTMF functions
- Emergency and Lone Worker functions
- 2-step low battery beep
- Customizable settings with PC programming software (free download)
- FCC Certified

Communication Range

Up to **250,000** sq ft in a building*  Up to **20** floors in a building*  Up to **2** miles in a work site* 

*Communication range may differ depending on operating environment or weather conditions, etc.

SPECIFICATIONS

| | |
|--|---|
| Usable frequencies (bandwidth) | 151.820 MHz (11.25 kHz), 151.880 MHz (11.25 kHz), 151.940 MHz (11.25 kHz), 154.570 MHz (20.00 kHz), 154.600 MHz (20.00 kHz) |
| No. of memory channels | 16 ch |
| Transmit output power | 2 W (High), 1 W (Mid), 0.5 W (Low) |
| Receiver sensitivity | 0.25 μ V (typical) for 12 dB SINAD |
| Squelch sensitivity | 0.25 μ V (typical) at squelch threshold point |
| Audio output power (at 5% distortion, 8 Ω load) | Internal SP 1.5 W (typical) External SP 0.4 W (typical) HM-222HLWP 1.5 W (typical) |
| Antenna impedance | 50 Ω |
| Power supply voltage | 7.2 V DC |
| Current drain | Receive stand-by 75 mA Receive max. audio 500 mA Transmit (High) 0.9 A |
| Dimensions (Projections not included) | 58 (W) \times 111 (H) \times 35.5 (D) mm, 2.3 (W) \times 4.4 (H) \times 1.4 (D) in (with BP-298) |
| Weight (Approximate) | 265 g, 9.3 oz (with BP-298) |

All stated specifications are subject to change without notice or obligation. Measurements made in accordance with TIA-603.

Applicable U.S. Military Specifications

| Standard | MIL 810G | |
|-------------------|----------|-----------|
| | Method | Procedure |
| Low Pressure | 500.5 | I, II |
| High Temperature | 501.5 | I, II |
| Low Temperature | 502.5 | I, II |
| Temperature Shock | 503.5 | I-C |
| Solar Radiation | 505.5 | I |
| Rain Blowing/Drip | 506.5 | I, III |
| Humidity | 507.5 | II |
| Salt Fog | 509.5 | - |
| Dust Blowing | 510.5 | I |
| Vibration | 514.6 | I |
| Shock | 516.6 | I, IV |

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

| Ingress Protection Standard | |
|-----------------------------|---|
| Dust & Water | IP54 (Dust-protection and splash resistant) |

Supplied Accessories:

- BP-298 Battery Pack • BC-240 Rapid Charger • BC-242 AC Adapter
- MB-124 Belt Clip • FA-SC28V Antenna

OPTIONAL ACCESSORIES

SPEAKER MICROPHONES



HM-222HLWP
High-power audio speaker with 3.5 mm earphone jack



HM-158LA
Compact speaker microphone with 3.5 mm earphone jack



HM-159LA
Loud and clear audio speaker microphone

HEADSETS



HS-94
Earhook type headset



HS-95
Neck-arm type headset



HS-97
Headset with throat microphone

PTT SWITCH CABLES



OPC-2004LA Plug adapter cable for VOX operation
VS-4LA PTT switch cable for manual PTT operation

(Either the VS-4LA or OPC-2004LA is required for use with the HS-94, HS-95 or HS-97.)

BATTERY PACK

BP-298 Li-ion, 2250 mAh (typ.), 2100 mAh (min.) (Same as supplied.)



OTHER ACCESSORIES

- MB-124** Belt clips (Same as supplied)
- FA-SC28V** Antennas 148-162 MHz (Same as supplied)

RAPID CHARGER



BC-242 **BC-240**

Charges the BP-298 in 3 hours (approx.). The BC-242 is supplied with the BC-240.

MULTI-CHARGER



BC-157S **BC-214N**

The BC-157S and AD-139 charger adapters are supplied with the BC-214N, depending on the charger version.

CIGARETTE LIGHTER CABLE & POWER SUPPLY CABLES

CP-23L For use with BC-240



OPC-515L For use with BC-240



OPC-656 For use with BC-214N



PROGRAMMING SOFTWARE & CABLE

CS-V3MR Programming software for Windows™ PC Available for free download from: https://www.icomjapan.com/support/firmware_driver/

OPC-478UC Programming cable (USB)

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. Windows is a trademark of the Microsoft group of companies. All other trademarks are the properties of their respective holders.

Your local distributor/dealer: