

VX-450 Series

VHF/UHF Portable Radios

SPECIFICATION SHEET

Durable On-the-Job Responsiveness

The industrial grade VX-450 Series maximizes worker uptime with expanded safety applications and convenient built-in features designed for heavy duty use.

Monitor Worker Safety

As with all Vertex Standard radios, the VX-450 series includes built-in Emergency and Lone Worker alerts. Emergency notification is user-initiated with a press of a button for the radio to switch to a designated channel and send an alert for help. Lone Worker mode is a built-in timer that requires the user to reset at a predetermined interval. If not reset, the radio automatically switches to Emergency mode to alert help.

When constant contact is required at all times, Vertex Standard's exclusive Auto-Range Transpond System (ARTS™) is included to inform the user that other ARTS™-equipped radios are within communication range.

No two job sites are alike and the optional Man Down function (with DVS-9 unit) is programmable to monitor a variety of worker timed safety scenarios vertically and horizontally as well as worker degree of motion. Adjusting the settings of the 3-axis sensor adapts the radio to each distinct work environment to monitor movement.

Solid Build for Extreme Environments

The VX-450 Series withstands job site abuse meeting military standards for ruggedness and meets the IP57 ingress protection standard where water does not harm the radio when submersed to a depth of 3 feet for up to 30 minutes.

Audio and Voice Responsiveness

Features 700 mW loud audio output ideal for noisy work environments.

Includes Channel Announcement which loudly speaks the channel description to simplify changing channels when focused on other tasks simultaneously.

Features voice activation (VOX) when used with MH-81A4B headset that enables users to transmit voice without pressing the Push To Talk button for hands-free operation.

Record and store up to 120 seconds of voice messages using the optional DVS-8 Voice Storage unit.

Built-in Selective Signaling Modes for Greater Flexibility

Includes MDC-1200® encode/decode along with both 2-tone and 5-tone encode/decode providing selective radio calling and efficiency in supporting a variety of discreet communications needs.

Large Group Communications Made Easy to Manage

Both the VX-459 and VX-454 radios have a massive 512-channel capacity and 32 groups to easily manage a variety of calls at the most complex job site or plant operation. The VX-459 also includes Direct Channel Entry to punch in the channel desired from the keypad for fast navigation.

FCC Narrowband Compliant

Meets the FCC Part 90 requirement for using 12.5 kHz channels by January 1, 2013.



The Vertex Standard Difference

Our number one goal is achieving superior customer satisfaction by delivering products and services that exceed your expectations. Vertex Standard radios are built to last and are backed by an industry-leading 3 year warranty – another great reason to choose Vertex Standard. Ask your Dealer for more details.



Top



VX-459

VX-454

VX-451

4.29" (H) X 2.3" (W) X 1.34" (D)



Additional Features

- Nine programmable keys (VX-459)
- Seven programmable keys (VX-454)
- Three programmable keys (VX-451)
- 8-Character alphanumeric display (VX-454/459)
- Voice inversion encryption
- Manual on/off encryption activation
- RX/TX Battery power save
- DTMF ANI
- DTMF Speed dial
- DTMF Paging
- CTCSS / DCS Encode and Decode
- Stun/kill/revive (5-tone)
- Comander
- Clear voice
- Whisper
- Minimum volume control
- Manual squelch adjustment
- BCLO, BTLO and TOT Functions
- Programmable LED color alert
- Priority scan
- Dual Watch scan
- Follow-me scan
- Talk Around scan
- Radio-to-radio cloning

Accessories

- MH-360S: Compact speaker microphone
- MH-37A4B: Earpiece microphone
- MH-450S: Speaker microphone
- MH-45B4B: Noise cancelling speaker microphone
- MH-81A4B: Over-the-head light duty VOX headset
- VH-110S: Over-the-head heavy duty dual-muff headset
- VH-115S: Behind-the-head headset w/boom mic
- VH-215S: Over-the-head single-muff headset
- VH-120S: Earpiece mic w/palm PTT switch
- VH-130S: Earpiece w/palm mic and PTT switch
- FNB-VI 13LI: 2400 mAh Li-Ion battery
- FNB-VI 12LI: 1170 mAh Li-Ion battery
- Desktop chargers available

Option Boards

- DVS-8: Digital voice storage unit
- DVS-9: Man down alert with digital voice storage

VX-450 Series Specifications

| | VHF | UHF |
|---|--|---------------|
| General Specification | | |
| Frequency Range | 134 - 174MHz | 450 - 512 MHz |
| Number of Channels and Groups | 512 / 32 Groups (VX-459, VX-454) 32 / 2 Groups (VX-451) | |
| Power Supply Voltage | 7.5V DC ± 20% | |
| Channel Spacing | 12.5 / 20 / 25 kHz | |
| PLL Steps | 1.25 / 2.5 / 5 / 6.25 kHz | 5 / 6.25 kHz |
| Battery Life (5-5-90 duty) | 18 hours (w/saver) / 16 hours | |
| 2400 mAh FNB-VI 13LI | 9.5 hours (w/saver) / 8.6 hours | |
| 1170 mAh FNB-VI 12LI | 18 hours (w/saver) / 15.6 hours | |
| | 9.2 hours (w/saver) / 8.3 hours | |
| IP Rating | IP 57 | |
| Operating Temperature Range | -22° F to +140° F (-30° C to +60° C) | |
| Frequency Stability | ±2.5 ppm | |
| RF Input-Output Impedance | 50 Ohms | |
| Dimension (H x W x D) | 4.29 x 2.3 x 1.34 inches (109 x 58.5 x 34 mm) (w/FNB-VI 12LI) 4.29 x 2.3 x 1.69 inches (109 x 58.5 x 43 mm) (w/FNB-VI 13LI) | |
| Weight (Approx.) | 10.44 oz (296 g) (w/FNB-VI 12LI, ANT, Belt Clip) 11.99 oz (340 g) (w/FNB-VI 13LI, ANT, Belt Clip) | |
| Receiver Specification: measured by TIA/EIA-603 | | |
| Sensitivity 12dB SINAD | 0.25 µV | 0.32 µV |
| Adjacent Channel Selectivity | 70 dB / 65 dB | |
| Hum and Noise | 45 dB / 40 dB | |
| Intermodulation | 70 dB / 65 dB | |
| Spurious and Image Rejection | 70 dB | |
| Audio Output | 700 mW (internal @ 16 Ohms, 5% THD) 500 mW (external @ 4 Ohms, 5% THD) | |
| Transmitter Specification: measured by TIA/EIA-603 | | |
| Output Power | 5 / 2.5 / 1 / 0.25 Watt (selectable by channel) | |
| Modulation | 16K0F3E, 11K0F3E | |
| Maximum Deviation | ± 5.0 kHz / ± 2.5 kHz | |
| Conducted Spurious Emissions | 70 dB below carrier | |
| FM Hum and Noise | 45 dB / 40 dB | |
| Audio Distortion | < 3 % @1 kHz | |

Applicable MIL-STD (Pending Test Completion)

| Standard | MIL 810C Methods/Procedures | MIL 810D Methods/Procedures | MIL 810E Methods/Procedures | MIL 810F Methods/Procedures | MIL 810G Methods/Procedures |
|-------------------|--------------------------------|--------------------------------|--------------------------------|---------------------------------|--------------------------------|
| Low Pressure | 500.1 / Procedure I | 500.2 / Procedure I, II | 500.3 / Procedure I, II | 500.4 / Procedure I, II | 500.5 / Procedure I, II |
| High Temperature | 501.1 / Procedure I, II | 501.2 / Procedure I, II | 501.3 / Procedure I, II | 501.4 / Procedure I, II | 501.5 / Procedure I, II |
| Low Temperature | 502.1 / Procedure I | 502.2 / Procedure I, II | 502.3 / Procedure I, II | 502.4 / Procedure I, II | 502.5 / Procedure I, II |
| Temperature Shock | 503.1 / Procedure I | 503.2 / Procedure I | 503.3 / Procedure I | 503.4 / Procedure I | - |
| Solar Radiation | 505.1 / Procedure I | 505.2 / Procedure II Cat. AI | 505.3 / Procedure II Cat. AI | 505.4 / Procedure I, II Cat. AI | - |
| Rain | 506.1 / Procedure I, II | 506.2 / Procedure I, II | 506.3 / Procedure I, II | 506.4 / Procedure I, III | 506.5 / Procedure I, III |
| Humidity | 507.1 / Procedure I, II | 507.2 / Procedure II, III | 507.3 / Procedure II, III | 507.4 / Procedure III | 507.5 / Procedure I, III |
| Salt Fog | 509.1 / Procedure I | 509.2 / Procedure I | 509.3 / Procedure I | 509.4 / Procedure I | 509.5 / Procedure I |
| Dust | 510.1 / Procedure I | 510.2 / Procedure I | 510.3 / Procedure I | 510.4 / Procedure I, III | 510.5 / Procedure I |
| Vibration | 514.2 / Procedure VIII, X | 514.3 / Cat. 10 | 514.4 / Cat. 10 | 514.5 / Cat. 20, 24 | 514.6 / Cat. 20, 24 |
| Shock | 516.2 / Procedure I, III, V | 516.3 / Procedure I, IV | 516.4 / Procedure I, IV | 516.5 / Procedure I, IV | 516.6 / Procedure I, IV |

Specifications are subject to change without notice or obligation.

VERTEX STANDARD is registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. © Vertex Standard Co. Ltd. 2010

NSS_450_10/2010